


# Sifang-4031-05 Down light SKD Specification



## Basic Information

Material: ADC12

IP: IP20

Application: Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment

Finish: Heat sink: Painting  
Reflector: Painting or Plating  
Spring: Stainless steel

## Product reference:

Model NO.	<b>Sifang-4031-05</b>
Finish	White
Material	Aluminum
COB LES	Φ6.0 mm
Compitable COBs	Citizen:1201/ CREE:1304/ Luminus:CXM-6 .etc
For COB Power ( W )	5.0 W
For Gross luminous flux	300 Lm
For Colour temperature	2700k, 3000k, 3500k, 4000k, 5000k
For Colour Rendering Index	CRI: 80+ / 90+
Optional Beam Angel ( ° )	15 °24 °38 °
Product size ( mm )	60*60*h75mm
Cut out	50*50mm
Mounting	Recessed Mounting
Application	Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment venues, etc.
SKD Included	IP: IP20; Sifang-4031-05 SKD Included: 1pc Heatsink Body (Painting Silver grey) ; 2pcs Middle ring ( Painting black) ; 2pcs Mounting Bracket ( Painting black) ; 1pc Face ring ( Painting White) ; 2pcs Reflector & 1pc Connector ; 1pc Cable clip
Inner Box ( mm )	95*95*95mm
QTY/CTN ( pcs )	50PCS/CTN
Outer box ( mm )	495*205*505mm
G.W/CTN ( kg )	7.5kg