


Sifang-4031-35 Down light SKD Specification





Basic Information

Material: ADC12

IP: IP20

Application: Offices, schools, shopping

malls, supermarkets, exhibition halls, home lighting, entertainment

Finish: Heat sink: Painting

Reflector: Painting or

Plating

Spring: Stainless steel

Product reference:

11044011010101001	
Model NO.	Sofamg-4031-35
Finish	White
Material	Aluminum
COB LES	Φ15.0 mm
Compitable COBs	Citizen:1204; CREE:1512/1816/1830; Luminus:CXM-14 .etc
For COB Power (W)	35.0 W
For Gross luminous flux	3000 Lm
For Colour temperature	2700k,3000k,3500k,4000k,5000k
For Colour Rendering Index	CRI: 80+ / 90+
Optional Beam Angel (°)	15 924 938 °
Product size (mm)	Ø185xH145
Cut out	120*120mm
Mounting	Recessed Mounting
Application	Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment venues, etc.
SKD Included	IP: IP20; Sifang-4031-35 SKD Included: 1pc Heatsink Body (Painting Silver grey); 2pcs Middle ring (Painting black); 2pcs Mounting Bracket (Painting black); 1pc Face ring (Painting White); 2pcs Reflector & 1pc Connector; 1pc Cable clip
Inner Box (mm)	140*140*165mm
QTY/CTN (pcs)	20PCS/CTN
Outer box (mm)	720*295*350mm
G.W/CTN (kg)	17.8kg